

## FASET Bulletin SN12 (Revision 3)

# Testing Requirements for Safety Net Attachment Devices

### The following principles should be included within the design:

All performance critical opening elements should require two consecutive deliberate manual actions to close and lock them. Non-performance critical elements shall be tested open.

### Test Procedure:

Select a statistically representative sample of attachment devices. Fit to each of the base materials for which they are intended, covering the manufacturers' defined range of sizes, load orientations, and methods of use, in accordance with the manufacturers' instructions. Connect a section of less than 1m of border rope to BS EN 1263-1. Apply an appropriate characteristic load through the border rope, inclined at 45° to the horizontal orientation of the device, at a cross head velocity of 1m/min (+/- 5%). Ensure that the device does not release the load.

Load a statistically representative sample to failure, or a multiple of the characteristic load. Observe and record the deformation and any mode of failure, to be used to advise on limitations on repeat use and removal from service after use in anger as appropriate.

Select a further statistically representative sample of attachment devices. Fit to the base material for its intended use as before, however all "location only" attachments must be left open. Apply a dynamic drop test as specified in latest version of BS EN 795 for Class A2 anchors directly to the attachment device.


Temporary or permanent deformation is permitted; however, the device must not release the load.

### Instructions for use and limitations must include the following:

- Specific instructions for application to the various base materials for which use is intended
- Any additional requirements that must be met to achieve performance
- Method of fitting the Safety Net
- Limitations on net type, extent of net sizing, method of connection
- Base material support limits and any member size limits
- The need for specific per-use / tamper checks prior to being "used"
- Maintenance needs, training needs, life expectancy and examination frequency
- Any ongoing testing needs and indications for removal from service
- Application specific information
- The need for confirmation of the suitability of the base material structure
- The need to monitor the installation to confirm correct application, including what to look out for



*Grippa*



*Lion Hook*



*Net Claw*

For more information about FASET, contact:

FASET  
PO BOX 138, WHITCHURCH  
SHROPSHIRE. SY13 9AD

T +44 (0)1948 780652  
E [enquiries@faset.org.uk](mailto:enquiries@faset.org.uk)  
W [www.faset.org.uk](http://www.faset.org.uk)

**FASET**  
Fall Arrest Safety Equipment Training